DIRECTIONS FOR USE


Use this product to remove nuisance and unsightly stumps. HI-YIELD® STUMP **REMOVER** decomposes the wood of tree stumps leaving them porous. The decomposition, depending on the size of the stump, may take several weeks or months. This allows for easy removal or burning of the stump. HI-YIELD® STUMP **REMOVER** is harmless to vegetation surrounding treated stumps. For removal of stumps up to 12" in diameter, drill a 1" hole in center of stump approximately 10" to 12" deep. Drill an additional 1" hole into the side of the stump approximately 3" below the top of the stump. This second hole should be slanted to connect (or nearly so) with the bottom of the center hole. Drill several sets of such holes for stumps larger than 12" wide.

Pour approximately 4 oz. of **HI-YIELD® STUMP REMOVER** into each hole. The product works best when weather is warm and stumps are dry. Fill each hole with water. Allow to stand from four to six weeks.

If stump is to be burned, refill holes with kerosene or fuel oil. Allow sufficient time for the liquid to be completely absorbed into the stump.

Then apply a slight amount of kerosene over stump and ignite. Or burn charcoal on top of stump or around base to start stump burning. The stump will burn with a smoldering, red glow, clear down to the roots, disintegrating the stump into ashes.





Stumps up to 12" in diameter

Stumps larger than 12' in diameter

CAUTION: Harmful if swallowed. Contains Potassium Nitrate. If swallowed give one or two glasses of water or milk and call physician. In the event of a medical or chemical emergency, contact Chemical.org/chemical.org/ North America 1-800-255-3924 or Worldwide Intl. + 01- 813-248-0585.

Hi-Yield® is a registered trademark of Voluntary Purchasing Groups, Inc.

32015-0815-CL



Hi-Yield*

Stump Remover



- The Easy Way To Remove Tree Stumps
- Decomposes Wood Of Unsightly Tree Stumps For Easy Removal Or Burning

CAUTION CAUTION

NET WEIGHT 1½LBS. (0.68 KG)

Manufactured By:

Voluntary
Purchasing
Groups, Inc.

230 FM 87 • BONHAM, TEXAS 75418 Visit Us At: www.hi-yield.com Product Questions? 855-270-4776